

DYN-6D1-1.

APPLICATION FOR

OF

**EMBOSSSED CARD PACKAGE PRODUCTION SYSTEM WITH MODULAR INSERTERS
FOR MULTIPLE FORMS AND CARD VERIFICATION APPARATUS**

S P E C I F I C A T I O N

TO WHOM IT MAY CONCERN:

Be it known that we, **Jeffery L. Hill, Gregory S. Hill, Robert J. Bretl** and **Fred J. Kassabian**, citizens of the United States of America, residents of Mundelein, Illinois; Lake Zurich, Illinois; Menominee, Michigan and Arlington Heights, Illinois, have invented a certain new and useful device in

**EMBOSSSED CARD PACKAGE PRODUCTION SYSTEM WITH MODULAR INSERTERS
FOR MULTIPLE FORMS AND CARD VERIFICATION APPARATUS**

of which the following is a specification:

CROSS-REFERENCES TO RELATED APPLICATION

Sub
C.1

This application is a continuation-in-part of U.S. Patent Application Serial No. 08/019,865 entitled "Automatic Embossed Card Package Production Apparatus and Methods" of Hill et al. filed February 19, 1993.

BACKGROUND OF THE INVENTIONField of the Invention

This invention generally relates to embossed card package production systems which produce card packages including embossed cards or the like mounted to pair card carrying matching forms, or carriers and, more particularly, to card inserters.

Description of the related art including information disclosed under 37 CFR 1.97-1.99

Embossed card production systems such as shown in U.S. patent No. 4,384,196 issued May 17, 1983 to McCumber et al. entitled "Apparatus and System for Preparing Data Cards and Mailer Forms and for Attaching Data Cards to Respectively Associated Mailer Forms" and U.S. patent No. B1 4,034,210 reexamination certificate issued February 7, 1984 to Hill et al. entitled "Credit Card Carriers and Methods of Manufacture" are known which automatically mount one or more embossed cards, such as plastic credit cards or the like, to corresponding card carrying mailing forms, or carriers, which, in turn, are "stuffed" into window mailing envelopes through which the name and address of the account holder printed on the carrier are viewable for mailing to the holder of the account associated with the cards enclosed in the carrier.

Each of the different types of known card package production systems and card inserters require a different kind

of form and, thus, there are a plurality of different types of carrier forms produced for use with these card package production systems. In order for card issuers to automatically issue cards using different types of carriers, it has been required for the issuer to produce and operate a different type of system for each different type of form. The versatility and thus value of these known monoform card package production systems has therefore disadvantageously been severely restrained.

Another problem with known embossed card package production systems is that the carriers which are employed all require the folding of a section of the body of the carrier over an edge of the card to hold the card within a slot or corner pockets. Such wedge trapping of cards disadvantageously require a larger carrier to form the folding section. In addition, when the carrier is unopened, it is no longer securely mounted to the carrier and is susceptible to inadvertent separation from the mailing carriers. Moreover, in known carrier forms with carrier pockets, the pockets are formed with diagonal cuts which require nonrotary oscillating members to open the card pockets to enable card insertion.

Another difficulty with known card production systems is the failure to obtain full verification of the correctness of the card embossment, the card magnetic stripe encoding and the information printed on the carrier. While in the card pack production system of Hill et al., U.S. patent No. B1 4,034,210 cited above, information from the embossed characters is compared with information automatically obtained from the carrier to determine there is a match, there is no independent verification of the correctness of the information. In the system of McCumber et al., on the other hand, no comparison is made between the card and carrier to determine if there is a match. Encoding on a magnetic stripe is compared against stored data for the card and an echo check determines whether an embossment has been made, there is no verification of whether the embossment is the correct embossment or whether it matches the encoding on the card; there is no verification of

whether the information printed on the carrier is correct or whether it matches either the embossed or encoded information on the card. Instead, correctness of embossed and printed information is assumed correct and a correct match is assumed by maintaining strict synchronization between production of cards and corresponding characters.

Another serious problem with the card package production system of McCumber et al. is that because of the synchronization require to hopefully obtain a match, it is necessary to insert incorrectly prepared cards, known to be incorrect because of incorrect magnetic stripe encoded information, into corresponding carriers. Although this incorrect card package is supposed to be automatically mounted to a reject station away from the correctly prepared package, if they are not separated, an incorrect package is easily combined with the correctly prepared packages.

Also, the versatility of the known card package production systems is severely limited due to the fact that it is usable with only a single type of inserter section which can process only single type of carrier.

SUMMARY OF THE INVENTION

It is therefore the principal object of the present invention to provide a card package production system with full verification which overcomes the disadvantages of known system by providing interchangeable inserter sections for mounting different cards to different types of forms and by providing means for mounting cards to carriers by means which does not rely upon wedge trapping by means of folded carrier sections or with pockets which cannot be releasably opened by means of rollers.

This object is achieved by provision of a card production system having an insertion station, means for delivering cards to the insertion station for insertion into carrier forms delivered to the insertion station and means for delivering the forms in a preselected orientation to a loaded carrier

Sub
C2

outlet with an interchangeable card insertion system, comprising a first type of insertion apparatus to insert cards into a first type of carrier form, means for releasably mounting the first type of insertion apparatus at the insertion station to mount cards to the first type of carrier form, a second type of insertion apparatus for mounting cards to a second type of carrier form and means for releasably inserting the second the type of insertion apparatus at the insertion station in lieu of the first type of insertion apparatus for inserting the cards into a second type of carrier form.

Also, the object of the invention is partly obtained by providing an embossed card package production system for mechanically mounting rectangular cards with four edges to carrier forms with an inserter for mounting cards to the carrier forms, comprising means for opening a pair of corner pockets in the carrier for receipt of a pair of corners of the card at opposite ends of one of the edges, means for inserting the pair of corners of the card into the corner pockets and means for moving a flap of the carrier over another one of the edges of the card opposite the one edge to releasably hold the pair of corners of the card in the corner pockets of the carrier.

Further, obtainment of the object is achieved partly by provision of an embossed card package production system for mechanically mounting cards to carrier forms with an inserter for mounting cards to the carrier forms, comprising means for opening a pair of corner pockets formed in part by elongate parallel side slots in the carrier form for receipt of opposing side edges at a pair of opposing corners of the card including a roller with a raised edge aligned adjacent at least one of the elongate parallel side slots while in contact with the body of the carrier and means for inserting the pair of opposing side edges at the opposing corners of the card into the corner pockets of the carrier.

Moreover, the object of the present invention is achieved by providing an embossed card production system having means

for accessing stored embossed card information and means for embossing a card with the stored embossed card information with an embossed card verification system, comprising means for reading the embossed information on the card, means for comparing the read embossed information on the card with the stored embossed information for the card to determine if there is a match and means responsive to the comparing means for automatically identifying each card for which the information embossed on the card does not match the stored embossed information for the card.

The object of the invention is also achieved by provision of a method of mounting cards to a plurality of different mailing forms, comprising the steps of (a) automatically mounting cards to a first type of mailing form with an automatic card mounting apparatus having an insertion station at which cards are mounted to forms, a card feeder for feeding cards to the insertion station and a forms feeder adapted to feed different types of mailing forms to the insertion station, (b) releasably mounting a first type of insertion apparatus at the insertion station to insert cards into a first type of carrier, (c) automatically mounting cards to the first type of carrier forms with the first type of insertion apparatus, (d) removing the first type of inserter from insertion station and mounting in its place a second type of insertion apparatus for inserting cards into a second type of carrier form and (e) automatically mounting cards to the second type of mailing forms by using the second type of insertion apparatus.

Still, the object of the invention is obtained by providing an embossed card package production system having means for producing cards from stored card information and means for inserting the cards into card carrying mailing forms with a verification system, comprising means for determining when a card has been incorrectly prepared and means for preventing an incorrectly prepared card from being inserted into a carrier.

BRIEF DESCRIPTIONS OF THE DRAWINGS

The foregoing objects and advantageous features of the invention will be explained in greater detail and others will be made apparent from the detailed description of the preferred embodiment of the present invention which is given with reference to the several figures of the drawing, in which:

Fig. 1 is a front view of the preferred embodiment of the embossed card pack production system;

Fig. 2 is an illustration of a card having a magnetic stripe and embossed character;

Figs. 3A and 3B are front views of preferred embodiments of different types of card carrier forms preferably used in the preferred embodiment;

Fig. 4 is a functional block diagram of the preferred embodiment of the embossed card pack production system illustrating the preferred steps for producing an embossed card pack;

Fig. 5A, B and C are flow charts showing the procedural steps of the card manufacture and insertion process of Fig. 1;

Fig. 6A is a schematic illustration of the operation of the card package production system when using carriers of the type shown in Fig. 3A;

Fig. 6B is a perspective view of the preferred embodiment of the inserter module folder, form rotation and form rejection units of Fig. 4 used for the carrier of Fig. 3A and corresponding to the embodiment illustrated in Fig. 6A;

Fig. 6C is an enlarged perspective view of the preferred embodiment of the portion of the inserter of Fig. 6B which bends the carrier to open the ears of the corner pockets for receipt of a card;

Fig. 6D is a partial perspective view showing how the flap of the carrier of Fig. 3A is bent to engage with the edge of the card during movement of corner pockets away from the

inserter;

Fig. 7A is a schematic illustration of the operation of the card package production system when using carriers of the type shown in Fig. 3B;

Fig. 7B is a perspective view of the preferred embodiment of the inserter module folder, form rotation and form rejection units of Fig. 4 used for the carrier of Fig. 3B and corresponding to the embodiment illustrated in Fig. 7A;

Fig. 7C is a perspective view of the position of the inserter of Fig. 7A at another stop step in the inserting sequence in which a card is held in preparation for engagement with a carrier form of the type shown in Fig. 3B;

Fig. 7D is a perspective view of the position of the inserter of Fig. 7C at a later step in the inserting sequence in which the card has been placed in the position for capture within the pockets of a carrier of the type shown in Fig. 3B;

Fig. 7E is another perspective view of the inserter of Fig. 7D at a later step in the inserting sequence in which the card is in position for capture by the carrier;

Fig. 7F is another perspective view like that of Fig. 7E but with the pocket being opened and about to receive the card; and

Fig. 7G is a perspective view of the inserter shown in Fig. 7F at a later step in the inserting sequence in which the card has been slipped into the corner pockets of the carrier of Fig. 3A.

DESCRIPTION OF THE PREFERRED EMBODIMENT

Referring to Fig. 1, the preferred embodiment of the embossed card package production system 10 functions to produce fully verified, embossed and encoded credit cards mounted to verifiably matched carrier forms, or carriers, with the account owner's name and mailing address printed thereon and inserted into window envelopes that are metered with appropriate postage and are ready for mailing.

The system 10 preferably includes a 486 DX computer 12

and an open reel tape drive 14 for controlling the operation of the system. A keyboard 13 is used for manual input of account data and control information into the computer 12. Information inserted into the computer 12 memory is shown at a display screen 16 of the system 10. An embosser section 20 embosses various alphanumeric characters 32 on the face of the card 30, generally the account number and name of the account owner associated with the card, and magnetically encodes like information on a magnetic stripe 35 on the back of the card 30. The embossed and encoded cards 30, Fig. 2, are carried from the embosser section 20 to a card inserter section 24. The inserter section 24 inserts correctly embossed and encoded cards 30 into verifiably matched and correctly printed carrier forms 26. The carrier forms 26 hold one or more embossed cards 30, Fig. 2, which are folded and stuffed into suitable window envelopes (not shown) at an envelope stuffer 34. The stuffed envelopes containing the carrier forms 26 with matching cards 30 are transported to a postage metering machine 18, Fig. 4 (not shown in Fig. 1), to print the appropriate mailing postage on the stuffed envelopes. The materials from which these embossed card packages are produced include blank carrier forms, or carriers, 26 and blank credit cards or like, such as shown in the U.S. patents noted above.

Sub C3 The carrier forms 26 are preferably one of those shown in Figs. 3A and 3B and a plurality of these interconnected carrier forms 26 are fanfolded like those shown in U.S. patent 4,034,210 issued July 5, 1977 to Hill et al., and as shown in Fig. 1, but are without marginal pin holes for pin drive feed mechanisms which are not employed in the ECPAP system 10. The printer 48 prints on both types of carrier forms the name and address 35 and bar code 27. The cards 30 with activation labels are mounted to the carrier by means of pockets cut into the plane paper holes 93. For further detailed information about the carrier of Figs. 3A and 3B, reference should be made to U.S. Patent Application Serial No. _____ of Hill et al. entitled "Card Carrier Forms For Automated Embossed Card Package Production System" filed March 24, 1993.


contemporaneously herewith. After having carrier information printed on the end one of a plurality of interconnected, fan folded carriers 26, a burster separates the end one from the others before cards 30 are inserted.

Referring to Fig. 2, the cards 30 have a field for receipt of embossed characters 32 and a magnetic stripe 35 for receipt of magnetically encoded magnetic stripe data relating to the account associated with the card. Common window envelopes which have transparent sections to enable viewing of the name and mailing address printed on the contents of the carrier mailing form are, of course, also provided as well as a full charge, or load, to the postage metering machine.

The system 10 housing contains a slide out drawer for holding the tape driver 14. The blank cards 30 are stacked in a hopper, or chute, 15 and are transported to the card embosser encoder section 20. The cards 30 are embossed with the stored card account information such as the account owner's name, address, card number and expiration date as seen in Fig. 2. The embosser section 20, Fig. 1, also magnetically encodes each card with information identifying the embossed card 30 on the magnetic stripe 35, Fig. 2, of the card. The embossed and encoded cards 30 which are correctly prepared are transported to a card labeler 60, Fig. 4, for automatic placement of removable stick-on activation labels 21 on the card 30. The adhered activation labels preferably are preprinted with a telephone number of the card issuer which the card owner calls upon receipt of the card pack through the mail to request activation of the card for use. The correctly prepared embossed cards 30 with the affixed activation labels are then passed to the card inserter 24 for placement in printed card carrier forms 26. In keeping with one aspect of the invention, labels are only applied to cards determined to be correctly prepared to avoid confusion between correctly and incorrectly prepared cards.

A fan folded stack of blank carrier forms 26 are carried through a forms printer 48 by a forms feeder in the card insertion module 24. The printer 48 prints account

information such as the card account owner's name, number and address at a name and address field 35 on the blank carrier forms 26A and 26B. Additionally, one of a plurality of different bar codes 27, such as interleaved two of five code, interleaved three of nine code, Codabar UPC-A&E code, EAN-8 code and EAN-13 code are used to encode the card account information printed on the form 26 such as the account number and name.

Sub C4  The plurality of fan folded carrier forms 26, once printed, are sent to a form burster 36. As noted, the form burster 36 separates the end printed carrier forms 26 from the fan folded plurality of carrier forms 26 to produce individual carrier forms. In addition, in the preferred embodiment, the form burster 36 carries a sensor for reading the code 27 from each carrier form 26 as it is separated from the fan carrier forms 26. For further information relating to the burster, reference should be made to U.S. Patent Application Serial No. _____ of Hill et al. entitled "Card Package Production System With Burster and Carrier Verification Apparatus" filed March 24, 1993, contemporaneously herewith. The separated carrier forms 26 are transported to the card inserter section 24 for receipt of the embossed cards 30. As many as four embossed cards are insertable into a single carrier form 26.

If the information embossed or encoded on the embossed card 30 is not correctly prepared or does not match the associated carrier form 26, the card 30 is sent to one of two reject locations 69 and 81, Fig. 4, without being mounted to a carrier 26 to avoid confusion. Likewise, carrier forms 26 which are not correctly prepared or do not match are rejected and sent to a rejected form location 90, Fig. 4, without having cards mounted to them to avoid confusion. Only correctly prepared carrier forms 26 containing correctly prepared and matching embossed cards 30 are folded and transported to the envelope stuffer 34. Only the envelopes with fully verified carriers are stuffed with the filled card carriers 26 and are transferred to a postage metering machine 18, Fig. 4, to place the appropriate postage on the envelope.

Referring now particularly to Fig. 4, card account data information is stored in a card account data memory 40, preferably a 330 Mbyte, 33 Mhz memory type for the 486 DX computer 12 made by Everex. The card account data for as many as 400,000 accounts are stored in the memory 40 with 870 bytes per account.

The account information preferably includes the name of the account, or owner of the account, the account number, the date of issuance, the date of expiration, the number of cards per account, the credit limit as well as other account information. The card account information stored in the card data memory 40 and the carrier form data stored in the form data memory 44 are selectively obtainable insertable from a number of different data input sources. A modem 22 inputs form and card data information over a telephone line from a remote computer (not shown) to the form data memory 44 and card data memory 40. Alternatively, a hardwire network 21 is used to transfer information from a plurality of computers for receipt at the system 10. Alternatively, a tape reel 14 or the like is employed for inputting card and carrier form data at the hard drive of the ECPAP system 10. This account information is organized in blocks relating to embossments, magnetic stripe encoding and carrier printing. At least some of the information of each block, such as the account number, must correspond or match some of the information of the other blocks.

Based on this account data and control information from manual inputs on the keyboard 13, Fig. 1, the system 10 produces the fully verified embossed card package comprising verified correct credit cards attached to verified correct carrier forms verified to match the attached cards within envelopes bearing postage and ready for mailing to the account owner at the name and address printed on the carrier. As noted, the verification is of the utmost importance to insure that only correctly embossed and correctly encoded cards are attached to matching carrier forms which bear the correct name and address of the account owner of the attached cards.

Accordingly, one separate data verification is performed on the forms 26 while three separate data verifications are performed on the cards in addition to matching verification between the carriers and matching cards.

Referring still to Fig. 4, the operation of the 10 is under control of a microprocessor based computer 12 which communicates with the various other functional blocks as indicated by broken line connections therebetween. Card flow between the functional blocks is indicated with solid line connection while carrier flow is indicated by solid bold line connections. The microprocessor 12 is preferably a model A80486DX-3301 or equivalent microprocessor made by Intel Corporation operating at thirty-three MHz, while the program memory 42 and thus data memory is contained in a single or multiple sectored hard drive having a storage capacity of 330 MBytes and preferably comprises a model LXT340A made by Maxtor Corp. An algorithm of the program stored in the program memory 42 pursuant to which the microprocessor 12 operates to control the remaining electromechanical elements of the system 10 is illustrated in Figs. 5A, 5B, 5C, 6 and 7 and by the listing of the preferred program for implementing the algorithm of Fig. 5A, 5B and 5C, attached hereto as Exhibit A.

Beginning with the flow of carriers 26, under control of the microprocessor 12, blank carrier forms 26 from a supply of fan folded forms 26 are then passed one at a time through a forms printer 48. A carrier form data memory 44 associated with the microprocessor 12 stores information for printing on the blank carrier forms 26. The forms printer 48 then prints on each form stored carrier form information taken from the form carrier data memory 44. This information is selected by the microprocessor 12 from the form carrier data memory 44 and relates to an associated account from the card data memory 40 including the name and mailing address of the account holder and also including other information such as the number of cards to be attached to the carrier form, the dates of issuance and expiration and the credit limit. In addition to the carrier data, the forms printer 48 under control of the

microprocessor 12 also prints the bar code 27 and preselected graphics in color, if desired, and other written information, such as the terms of the agreement, which have been preselected for all or a batch of carriers stored in carrier graphics and carrier printing sections of the carrier form data memory 44. Alternatively, preprinted carrier forms 27 with the preprinted carrier account data on the forms are send directly to the form bar code reader 38 and are used for receipt of embossed cards 30 in the system 10.

Sub C5 [The carrier account information which is unique to each carrier 26 is also preferably printed in a machine readable format such as a standard bar code 27. In keeping with one of the aspects of the invention, multiple types of bar codes are decodable by bar code reader 38 for enhanced versatility. After the indicated carrier account data has been printed on a carrier 26, such as shown in Figs. 3A and 3B, the printed carrier is passed via a path 50, to a form bar code reader 38 which photoelectronically senses the bar code associated with the printed account carrier information from each carrier 26.

Obtaining one aspect of the carrier form bar code reader 38 preferably decodes the following bar codes: interleaved two of five code, interleaved three of nine code, Codabar UPC-A&E code, EAN-8 code and EAN-13 code. The preferred apparatus for sensing and decoding is shown and described in the aforementioned U.S. Patent Application Serial No. _____ of Hill et al. entitled "Card Package Production System With Burster and Carrier Verification Apparatus" filed March 24, 1993, contemporaneously herewith. The read carrier information is passed via a suitable two way communication path 52 to the microprocessor 12 which compares it to the stored carrier information sent to the forms printer 48 via a communication path 54 to determine if there is a match. If the carrier account information read from the carrier 26 is the same as the carrier data obtained from the form data memory 44, then there will be a match and the correct printing of the carrier 26 is verified. In that event, and if there is a match with card information on a card 30 presented for

attachment to the carrier 26, the printed forms continue through the form burster 36, the forms feeder-card inserter 24, the form folder 86, the form rotation block 88 to a card package outlet 55 to a form transporter 92 to move it to the envelope stuffer 34, then to the inserter 24 where they are mated with one or more verified and matching cards.

Sub C6

If, on the other hand, the carrier account information read from a carrier 26 does not match the carrier information stored in the carrier form data memory 44, then achieving another objective of the invention, the carrier advantageously is sent to a carrier form rejection area 90 to prevent the incorrect form from being stuffed into an envelope. The carrier 26 passes through the form burster 24 to the forms feeder-card inserter, or inserter, 24, while the card inserter is inhibited from mounting a card. The mismatched or incorrect carrier passes through the inserter 24 without receiving a card. It then passes through the form folder 86 and at the form reject rotation unit 88 it is pushed along path 87 to the form reject location 90. While other bar code readers could be utilized, preferably the form bar code reader 38 is preferably made by Opto Technology as part number QTR while preferably the decoding is performed by a forty pin IC made by Hewlett Packard under part number HBCR-1800.

Reference should be made to U.S. Patent Application Serial No. _____ of Kassabian et al. entitled "Card Package Production System With Modular Carrier Folding Apparatus for Multiple Forms" filed March 24, 1993, contemporaneously herewith, for further information relating to the preferred form of the apparatus for rejecting the incorrect carriers.

While the carrier forms 26 pass through the forms printer 48 and to the inserter 24, the cards 30 make a similar journey from a stack of cards 30 through a blank cards feeder 58, a card graphics module 62, a card embosser/encoder/infill unit 20, an on line jitter tester 82, an embossed card mag stripe reader 57, an embossed card transporter, a card mag stripe reader 64, an embossed character reader 70 and a labeler to the card inserter 24.

The blank cards feeder 58 passes blank cards one at a time to a card graphics module 62 which inputs graphic lettering and designs selectively in color on the blank card surface. The card embosser 20 is preferably of the general type shown in U.S. patent 4,969,760 issued November 13, 1990 to LaManna et al., or the like. The selected card graphics and card printing information is stored in a card graphics and card printing data section of the program memory 42 and relates to information that applies to all cards or a batch of cards and is not unique to each card, as distinguished from the card account data.

The card embosser 20 embosses the card account embossed information into each card in accordance with continued inputs sent via a communication path 68 which are determined by the microprocessor 12 from the card account embossed data section of the card data memory 40. The embossed card 30 is then sent to the card magnetic stripe encoder of the embosser/encoder unit 20 which encodes the magnetic stripe 35, Fig. 2, on the card 30 with magnetic stripe card information received on the communication path 68 from the microprocessor 12 which, in turn, it obtains from a magnetic stripe card encoding data section of the card data memory 40.

An embossed card magnetic stripe reader 57 reads and decodes information encoded on the magnetic stripe 35, Fig. 2, of the card 30 and compares it with the card account embossed information sent from the card data memory and read by the embossed character reader 70, Fig. 4. In addition, the read encoded information is compared to the encoded account information stored in card data memory 40 used to encode the card. If the encoded information on the magnetic stripe 35, Fig. 3, does not match stored card account information, does not match the embossed information read from the card or the embossed information read from the card does not match the stored embossed account data, then the embossed and encoded card 30 is sent to an embosser card reject area 69. Since the card is incorrectly encoded, it is advantageously prevented from being inserted into a carrier form 26 and stuffed into an

envelope to achieve one aspect of the objective of the invention. If the card is correctly encoded, based on the reading by the embosser card M/S reader, the embossed and encoded cards 30 are then moved via the embossed/encoded card transporter 66 to the card magnetic stripe, or M/S reader 64, and the card embossed character reader 70 which respectively receives what is read by each via paths 72 and 74 and makes comparison to account data stored in the card data memory for each and also compares what is read by each to each other. The embossed character reader 70 is preferably of the type shown in U.S. patent B1 4,194,685 of Hill et al. entitled "Verifying Insertion System Apparatus and Method of Operation" issued March 25, 1980, reissue certificate issued February 19, 1985.

While other devices could be used successfully, preferably the embossed character reader 70 is made by Dynetics Engineering Corporation and is shown in U.S. Patent No. 4,215,813, while the magnetic stripe reader 64 is preferably made by Brush Industries under part number 901-529-0.

Coupled with the 486 DX computer 12 is a manually operated card jitter tester and analyzer 80 quality check tool built by Q-Card Corp. of Owings Mills, Maryland. A card is manually run through the jitter tester 80 and the computer 12 analyzes the encoding at seventy-five bits per inch of the card for track one and two hundred ten bits per inch for tracks two and three. The card jitter tester and analyzer 80 graphically displays a JT1A report on the display screen 16, Fig. 1, or on a print out indicating if the tested card has been properly encoded. Alternatively, an on line jitter tester 82 is placed for receipt of cards exiting the card embosser/encoder 20. Prior to carrying the embossed and encoded cards 30 to the card labeler 60 by the transporter 66, the on line card jitter tester and analyzer 82 reads the cards to verify proper encoding. Preferably, the jitter tester and analyzer 80 is like one made by Q-Card Company of Owings Mills, Maryland and the on line jitter tester 82 is the same as

jitter tester 80 but with a computer interface and automatic card transporter provided.

The microprocessor 12 compares each reading of the embossed information on the card 30 by the photoptical embossed character reader 70 and the magnetic stripe reader 64 to the account data information stored in the appropriate section of the data memory 40 and to each other. Advantageously, the information decoded from the magnetic stripe 35, Fig. 2, of the card 30 by the magnetic stripe reader 64 is compared with the embossed card character information read by the embossed character reader 70 to determine if there is a match. If there is a match of information, the card 30 is internally verified to be correct, and is passed to the inserter 24. If the coded information from the magnetic stripe reader 64 does not match the embossed character information on the card read by the embossed character reader 70 do not match each other, then the microprocessor 12 identifies the card as being incorrectly embossed or encoded and the card is rejected before insertion into a carrier.

After checking the embossed cards 30 for correctness and automatically rejecting the identified incorrect cards, the card transporter 66, under the control of the microprocessor 12, enables the card labeler 60 to label only those. The card labeler 60 automatically applies removable informational labels, such as stick-on card activation labels 21, Figs. 3A and 3B, to only the correct cards 30. The computer 12 through means of card labeler 60 or, alternatively, the card labeler itself, accumulates information concerning the total number of informational labels applied to the cards 30 and the total number of correct cards. The passing of the correct cards 30 to the labeler is selectively performed either manually or automatically in a single card production apparatus 10, while the labeling is produced only automatically and only on verified correct cards. In this way, correct cards with labels are readily distinguished from rejected cards without labels.

The inserter 24, under control of reports from the microprocessor 12 via a communication path 76 causes the internally verified card 30 to be mounted to a matching carrier 26. Advantageously, the microprocessor via communication path 52 compares the coded carrier information read from the form bar code reader 38 with the coded card information read from the magnetic stripe reader 64 and the embossed information read by the embossed character reader 70 to determine if there is a match and thereby eliminates the need for synchronization between card and carrier production to achieve a match without verification. Advantageously, the card inserter 24 rejects the cards 30 which do not match the carrier information decoded from the carrier 26 before insertion into a carrier. The nonmatching cards are sent to an inserter card reject area 81 and the empty carrier 26 is separately sent to a carrier form reject area 90. Cards 30 having information which does not match the carrier information or the stored account information are prevented from being inserted into the corresponding carrier at the card inserter 24. The embossed cards 30 which have card information that do match the decoded carrier information are mounted to the matching carrier 26 at the card inserter 24.

One or more cards 30 are selectively insertable into a single matching carrier form 26. The automatic card mounting apparatus or card inserter 24 is located at an insertion station at which cards 30 are mounted to carrier forms 26 including those shown in Figs. 3A and 3B. The embossed card package production system 10 routes cards 30 to a plurality of different carrier mailing forms 26. Referring to Figs. 3A and 3B two types of carrier forms 26A and 26B employed in the system 10, Fig. 1, are shown holding embossed cards 30. The first type of form 26A, Fig. 3A, is flexible planar body 93 having a pair of spaced parallel ear shaped slots, or corner pockets, 28 for receipt of the sides 31 of a card 30 and one of either the top or the bottom of the card. The form 26A has a bottom flap, or lip, 33 for receipt of the other of the top or bottom of the card 30. The corner pockets 28 and the lip

33 are cut from the flexible planar body 93. The card 30 is held between the pockets 28 and the lip 33 at a location spaced from the periphery of the body 93. The corner pockets 28 hold the card 30 against movement in three of four possible rectilinear directions. The lip 33 engages with an edge of the card 30 and is intermediate to the corners of the card to hold the card 30 against movement in the fourth possible rectilinear direction.

Sub C7
A second type of carrier form 26B seen in Fig. 3B has a flexible planar body 93 with a pair of parallel spaced side slot sections 29 and a fold 89 to hold the card 30 within the side slots. The mailing form 26B has a pair of rectilinear slots 39 cut in the body 93 to form a pair of opposed corner pockets for receipt of opposed corners 41 of the card 30. The rectilinear slots 39 have a pair of parallel spaced slot sections 29 and a cross slot section 43 transversely extending between the pair of parallel spaced slot sections 29. In the form of Fig. 3A, the corner pockets open away from the leading end section and the address and toward the bar code field 27 while in the carrier of Fig. 3B, the address is located on the lagging end section while the pockets face toward the bar coding and away from the leading edge.

Reference should be made to U.S. Patent Application Serial No. _____ of Hill et al. entitled "Card Carrier Forms For Automated Embossed Card Package Production System" filed March 24, 1993, contemporaneously herewith, for further details about each of these different types of carriers.

In the system 10 a card feeder or transporter 66 feeds cards 30 to the insertion station at which a card inserter 24 is located. The card inserter module 24 includes a forms feeder adapted to feed the different types of mailing carrier forms 26A and 26B from the fan of folded carriers to an insertion station. A first type of card insertion apparatus 24 is releasably mounted at the insertion station to insert cards 30 into one type of form carrier 26A. The card inserter 24 automatically mounts embossed cards 30 to the first type of carrier forms 26A. To insert cards 30 into a different or

second type of carrier 26B in the ECPAP system 10, the first type of inserter is removed from the insertion station and mounted in its place is a second type of card insertion apparatus for inserting cards into the second type of carrier form 26B. The embossed cards 30 are automatically mounted to the second type of carrier mailing form 26B by using the second type of insertion apparatus.

Sub C8

After all the cards 30 have been attached to a matching carrier form 26, the inserter 24 passes the filled carrier form via path 84 to a form folder 86. The form folder 86 folds the loaded carrier 26 along two perforation lines 89, Fig. 3, to divide the carrier into three equal areas. As with the inserters, two different types of folders are alternatively employed for folding different types of carriers. The folded carrier forms 26 are rotated by an arm at a form rotation station 88 for insertion into mailing envelopes. Before being rotated, the form of Fig. 3A is flipped over after folding while the form of Fig. 3B does not and therefore different folders are used when there are different carrier forms. Empty carrier forms 26 which do not match with a corresponding card or are otherwise improperly prepared are sent via a transportation path 87 to a form reject area 90 to avoid placement into mailing envelopes. The preferred embodiment of the form folder 86, form rotation unit 88, form reject unit 90 and form transporter to envelope stuffer 92 are shown in U.S. Patent Application Serial No.

_____ of Kassabian et al. entitled "Card Package Production System With Modular Carrier Folding Apparatus For Multiple Forms" filed March 24, 1993, contemporaneously herewith, and reference should be made thereto for details of how the different carriers of Figs. 3A and 3B are folded different to point them both to the envelope stuffer in the correct orientation.

Folded carriers 26 with correctly matched embossed cards 30 are carried along a form transporter 92 to the envelope stuffer 34. The envelope stuffer 18 preferably used is a Pitney Bowes Spectrum Model F400. The envelope stuffer 34

places the filled and folded carrier form 26 into a window envelope from a supply of window envelopes. The stuffed envelopes are then sealed and passed to a postage metering machine (not shown) which applies correct postage to the envelope. The postage metering machine used is preferably one made by Pitney Bowes such as Paragon Mail Processor Model Nos. USS4 - USS9, Eagle Model E660 or E670, or a Model 5300 or 5636.

Sub C

Also preferably performed in the embossed card package production apparatus 10 is a method of mounting cards to a plurality of different mailing forms, comprising the steps of (a) automatically mounting cards to a first type of mailing form with an automatic card mounting apparatus having an insertion station at which cards are mounted to forms, a card feeder for feeding cards to the insertion station and a forms feeder adapted to feed different types of mailing forms to the insertion station, (b) releasably mounting a first type of insertion apparatus at the insertion station to insert cards into a first type of carrier (c) automatically mounting cards to the first type of carrier forms with the first type of insertion apparatus,

(d) removing the first type of inserter from insertion station and mounting in its place a second type of insertion apparatus for inserting cards into a second type of carrier form and (e) automatically mounting cards to the second type of mailing forms by using the second type of insertion apparatus. For details of the methods of operation, reference should be made to U.S. Patent Application Serial No. _____ of Hill et al. entitled "Automatic Verified Embossed Card Package Production Methods" filed March 24, 1993, contemporaneously herewith.

Also, performed in the embossed card package production apparatus 10 is an improved verification system, comprising means for determining when a card has been incorrectly prepared and means for preventing an incorrectly prepared card from being inserted into a carrier.

Referring now to Fig. 5A, the computer 12 retrieves customer account information in step 100 including the name of

the customer, the account number, the date of issuance, the date of expiration as well as other information. In step 102 the account information is transferred to the embosser while in step 108 the form printer receives the customer mailing information. In step 104 the blank card is embossed and the magnetic stripe encoded with the account information while in step 110 the form is printed with the customer mailing information.

In step 106 the card is read back and verified with the computer file while in step 112 the form is separated from the stock and read at the bursting station. In step 114 the computer file, the embossed card information read from the card, the encoded information read from the card, and the printed information read from the carrier form are all compared together to determine if there is a match. In step 116 a determination is made as to whether all the information is correct.

Referring now also to Fig. 5B, if all the information is not correct, the error is processed in step 118. In step 120 the counter verifies if the embossing and encoding are correct. If an error is detected, in step 122 the counter will cause rejection of the card and will then in step 124 cause a new card to be embossed and encoded. In step 126, after the new card is prepared, the counter returns to step 114 to compare the new card to determine if the new card has been properly prepared.

If in step 121 the card is verified to be prepared correctly, in step 128 the form will reread and in step 130 a comparison will be made to verify if the form and computer file match. If the form matches the file, the form and card are then processed in step 120 detailed in Fig. 5C.

If the form is correct, the form is ejected in step 132, a new form is printed in step 134, and the new form is read in step 136. In step 138 the new form is compared to the data file. If the file matches the form, a decision is made to process the card and form. If a discrepancy still occurs, the microprocessor based computer will stop the operation in step

140 and operator intervention is required.

Referring now to Fig. 5C, if the embossed encoded card, the printed carrier form and the information in the computer file match and a decision has been made to process in step 120, in step 142 the computer 12 causes the cards to be inserted into the carrier form and then in step 144 fold the carrier forms are folded closed for insertion into envelopes.

The forms are then turned ninety degrees in step 146 so that the forms are in proper alignment for insertion into an envelope by an envelope stuffer.

In step 148 the computer 12 checks if the envelope stuffer is ready for receipt of a form. If not ready, the computer 12 pauses in step 156 to allow the operator readies the stuffer in step 158. After it is determined in step 148 that the envelope stuffer is ready, the stuffed carrier forms are sent to the envelope stuffer in step 150.

The microprocessor based computer 12 selects the next customer account record in step 152 and returns to the start process 100, Fig. 5A, in step 154.

Referring now to Fig. 6A, a preferred embodiment of the portion of the card package production system 10 following the embossed/encoded card transfer 66 from the card embosser 20 is schematically illustrated with the card inserter function 24, as well as the form folder function 86, performed by an inserter apparatus 24A and a folder apparatus 86A especially adapted to insert cards into and fold carriers of the type shown in Fig. 3A.

The cards 30 come down a slide 160, are transported past the mag stripe reader 64 and embossed character reader 20 to the second of two card loading stations 162 and 164 at the inserter 24A, if the card is to be loaded into the second of two card mounting locations 166 and 168. If not, the card 30 is moved only to the first loading station 162 to be mounted into card mounting location 166.

A fan folded plurality of interconnected carrier forms 26A and moved to the burster 36 after being printed with carrier information by the forms printer 48. The bar code 27

Sub
C101

printed on the carrier is read during the bursting operation.

After the cards 30 are verified and the carrier 26A has been verified, the end carrier form 26A is forced to conform to the cylindrical surface of a roller 170 which causes the ears of corner pockets 31 to open and pusher members 172 and 174 to push the cards into the corner pockets. The carrier form continues to roll away from the inserter with the cards in the pockets and the lip 33 on the card then prints up and over the edge of the card 30 to hold it within the pockets 31, as best seen in Fig. 6F. The form is then pushed against a pivotally mounted stop member 176 until the leading end section 178 and middle card carrying section 180 buckle along fold line 89 away from the folding path 182. A pusher arm 184 then pushes against the middle section 180 adjacent the lagging fold line 89 until the carrier 30 is completely folded as shown. A pushing member 186 then pushes the folded carrier against a pivot pin 188 to rotate the folder form at the form rotation station 88. The folded form is then moved along a path 190 by pusher 191 toward an envelope stuffer 34 (rotation) or to an output stack of loaded carriers 26A' to the front reject location 90 (not shown).

Still referring to Fig. 6A, if the card 30 is not prepared correctly or does not match the carrier, then the rejected cards 301 are moved past the insertion stations 162 and 164 and down a chute 192 to prevent it from being loaded into a carrier 26A.

Referring to Fig. 6B, similar action is taken with a carrier which is incorrectly prepared or does not match a card. In that event, no card 30 is loaded prior to passing the carrier 26A through the folder 86A and to the form rotation module 88. However, instead of the pushers 191 pushing the empty carrier along path 190 as shown in Fig. 6A, the pusher 191 only pushes the empty carrier 26A into the path 194 of the pusher 186 which then pushes it away from the path 190 to the form reject location 90 (not shown) in the direction of arrow 193.

Referring now to Figs. 6C, D and E, the preferred

embodiment of the inserter 26A module and folder 86A module is shown in which a pushing apparatus 202 for pushing the folded carrier is to a load position. The card 30 is moved by a conveyor belt of the card transporter 66 to the carrier loading positions when they are pushed into the pockets of the carriers 26A held below a roller 198 and a roller 200.

Referring to Figs. 6D and E, it is seen how the ears 210 of the pockets 28 open to receive the card 30 as the carrier is turned below rollers 198 and 200, Figs. 6B and 6C. In Fig. 6E, the flap 33 is shown resiliently flowing up and over the edge of the card 30 as the adjacent portion of the carrier 26A is bent passing the roller 198. The roller 200 is driven by a motor 214 controlled by the computer 12.

Referring now to Fig. 7A, a preferred embodiment of the portion of the card package production system 10 following the embossed/encoded card transfer 66 from the card embosser 20 in which the card inserter function 24 as well as the form folder function 86 are performed by an inserter apparatus 24B and a folder apparatus 86B which are especially adapted to insert cards into the carrier of the type shown in Fig. 3B. As seen from a comparison of Figs. 6A and 7A, the remainder of the system 10 remains the same and the inserter 24A and folder 86B are directly substitutable for the member 26A and folder 86A since they both receive cards and carriers in the same way and in the same location and output loaded carriers to an envelope stuffer in the same orientation, direction and location. The modules containing different inserters and folders are of the same size and adapted to releasably fit with the other elements of the system to enable them to be interchanged so that the multiple forms of different types can be processed in the one system.

Because the carrier form 26A operates differently and because the address 35 is located on the end panel separate the one on which the address is located on the carrier form 26A, the carrier form 26B is folded differently and is flipped over on its side before being passed to the form rotation module and the envelope stuffer 34.

The feeding of the card 30 and the carrier 26B to the inserter 24B and the reject of incorrect cards 30 and incorrect carriers 26B is performed the same way as with the inserter 24A and fold 86A as shown in Figs. 6A, 6B and 6C.

Presuming that neither the card nor the carrier are rejected, the cards 30 are held by a card holding mechanism 196 where they are held until the carrier 26B moves by in the direction of arrow 308. The pockets are opened by rollers 300 and 310. The loaded carrier are then pushed up a guide wall 312 to a stop member at the top of the guide wall. In this position, the leading fold line is aligned with a folding gap at the base of the wall 312 and continued pushing causes it to buckle at the leading fold line and pass through the gap fold line first.

The folded edge of the carrier 26B is then engaged by a stop member 314. Another pushing member (not shown) then pushes the lagging edge of the carrier form along the folding path 182 until it tips over the stop member 314 as shown by arrow 316. The address in the lagging panel now faces upward, and the carrier 26B is turned and moved to the envelope stuffer as previously described with reference to Fig. 7A, etc.

Sub C11

Referring now to Fig. 7B, the cards 30 are moved into engagement with a card holding assembly 206 after they are moved there by a card conveyor 202 which drive the cards toward the card holding assembly 206 by means of a pulley 201 powered by a motor 204 under control of the computer 12. The card holding apparatus 196 has a hinge plate 206 with a pair of legs 208 upon which the cards are supported as best seen in Fig. 7E. As seen in Figs. 7G and 7F, the carrier travels adjacent a roller 320 which opens the pocket of the carrier 26B. The card is first moved to the position shown in Fig. 7C. Once moved past the legs 208, the plate 206 pivots to drop the card 30 into the carrier as shown in Figs. 7E and 7G.

In Fig. 7C the cards are moved into loading position adjacent the card holding apparatus 194 by the pushing member, associated with the conveyor belt 322, Fig. 7C.

While a detailed description of the preferred embodiment of the invention has been given, it should be appreciated that many variations can be made thereto without departing from the scope of the invention as set forth in the appended claims.

11
12
13
14
15
16
17
18
19
20
21
22
23
24
25
26
27
28
29
30
31
32
33
34
35
36
37
38
39
40
41
42
43
44
45
46
47
48
49
50
51
52
53
54
55
56
57
58
59
60
61
62
63
64
65
66
67
68
69
70
71
72
73
74
75
76
77
78
79
80
81
82
83
84
85
86
87
88
89
90
91
92
93
94
95
96
97
98
99
100
101
102
103
104
105
106
107
108
109
110
111
112
113
114
115
116
117
118
119
120
121
122
123
124
125
126
127
128
129
130
131
132
133
134
135
136
137
138
139
140
141
142
143
144
145
146
147
148
149
150
151
152
153
154
155
156
157
158
159
160
161
162
163
164
165
166
167
168
169
170
171
172
173
174
175
176
177
178
179
180
181
182
183
184
185
186
187
188
189
190
191
192
193
194
195
196
197
198
199
200
201
202
203
204
205
206
207
208
209
210
211
212
213
214
215
216
217
218
219
220
221
222
223
224
225
226
227
228
229
230
231
232
233
234
235
236
237
238
239
240
241
242
243
244
245
246
247
248
249
250
251
252
253
254
255
256
257
258
259
260
261
262
263
264
265
266
267
268
269
270
271
272
273
274
275
276
277
278
279
280
281
282
283
284
285
286
287
288
289
290
291
292
293
294
295
296
297
298
299
300
301
302
303
304
305
306
307
308
309
310
311
312
313
314
315
316
317
318
319
320
321
322
323
324
325
326
327
328
329
330
331
332
333
334
335
336
337
338
339
340
341
342
343
344
345
346
347
348
349
350
351
352
353
354
355
356
357
358
359
360
361
362
363
364
365
366
367
368
369
370
371
372
373
374
375
376
377
378
379
380
381
382
383
384
385
386
387
388
389
390
391
392
393
394
395
396
397
398
399
400
401
402
403
404
405
406
407
408
409
410
411
412
413
414
415
416
417
418
419
420
421
422
423
424
425
426
427
428
429
430
431
432
433
434
435
436
437
438
439
440
441
442
443
444
445
446
447
448
449
450
451
452
453
454
455
456
457
458
459
460
461
462
463
464
465
466
467
468
469
470
471
472
473
474
475
476
477
478
479
480
481
482
483
484
485
486
487
488
489
490
491
492
493
494
495
496
497
498
499
500
501
502
503
504
505
506
507
508
509
510
511
512
513
514
515
516
517
518
519
520
521
522
523
524
525
526
527
528
529
530
531
532
533
534
535
536
537
538
539
540
541
542
543
544
545
546
547
548
549
550
551
552
553
554
555
556
557
558
559
560
561
562
563
564
565
566
567
568
569
570
571
572
573
574
575
576
577
578
579
580
581
582
583
584
585
586
587
588
589
590
591
592
593
594
595
596
597
598
599
600
601
602
603
604
605
606
607
608
609
610
611
612
613
614
615
616
617
618
619
620
621
622
623
624
625
626
627
628
629
630
631
632
633
634
635
636
637
638
639
640
641
642
643
644
645
646
647
648
649
650
651
652
653
654
655
656
657
658
659
660
661
662
663
664
665
666
667
668
669
670
671
672
673
674
675
676
677
678
679
680
681
682
683
684
685
686
687
688
689
690
691
692
693
694
695
696
697
698
699
700
701
702
703
704
705
706
707
708
709
710
711
712
713
714
715
716
717
718
719
720
721
722
723
724
725
726
727
728
729
730
731
732
733
734
735
736
737
738
739
740
741
742
743
744
745
746
747
748
749
750
751
752
753
754
755
756
757
758
759
760
761
762
763
764
765
766
767
768
769
770
771
772
773
774
775
776
777
778
779
780
781
782
783
784
785
786
787
788
789
790
791
792
793
794
795
796
797
798
799
800
801
802
803
804
805
806
807
808
809
810
811
812
813
814
815
816
817
818
819
820
821
822
823
824
825
826
827
828
829
830
831
832
833
834
835
836
837
838
839
840
841
842
843
844
845
846
847
848
849
850
851
852
853
854
855
856
857
858
859
860
861
862
863
864
865
866
867
868
869
870
871
872
873
874
875
876
877
878
879
880
881
882
883
884
885
886
887
888
889
890
891
892
893
894
895
896
897
898
899
900
901
902
903
904
905
906
907
908
909
910
911
912
913
914
915
916
917
918
919
920
921
922
923
924
925
926
927
928
929
930
931
932
933
934
935
936
937
938
939
940
941
942
943
944
945
946
947
948
949
950
951
952
953
954
955
956
957
958
959
960
961
962
963
964
965
966
967
968
969
970
971
972
973
974
975
976
977
978
979
980
981
982
983
984
985
986
987
988
989
990
991
992
993
994
995
996
997
998
999
1000
1001
1002
1003
1004
1005
1006
1007
1008
1009
1010
1011
1012
1013
1014
1015
1016
1017
1018
1019
1020
1021
1022
1023
1024
1025
1026
1027
1028
1029
1030
1031
1032
1033
1034
1035
1036
1037
1038
1039
1040
1041
1042
1043
1044
1045
1046
1047
1048
1049
1050
1051
1052
1053
1054
1055
1056
1057
1058
1059
1060
1061
1062
1063
1064
1065
1066
1067
1068
1069
1070
1071
1072
1073
1074
1075
1076
1077
1078
1079
1080
1081
1082
1083
1084
1085
1086
1087
1088
1089
1090
1091
1092
1093
1094
1095
1096
1097
1098
1099
1100
1101
1102
1103
1104
1105
1106
1107
1108
1109
1110
1111
1112
1113
1114
1115
1116
1117
1118
1119
1120
1121
1122
1123
1124
1125
1126
1127
1128
1129
1130
1131
1132
1133
1134
1135
1136
1137
1138
1139
1140
1141
1142
1143
1144
1145
1146
1147
1148
1149
1150
1151
1152
1153
1154
1155
1156
1157
1158
1159
1160
1161
1162
1163
1164
1165
1166
1167
1168
1169
1170
1171
1172
1173
1174
1175
1176
1177
1178
1179
1180
1181
1182
1183
1184
1185
1186
1187
1188
1189
1190
1191
1192
1193
1194
1195
1196
1197
1198
1199
1200
1201
1202
1203
1204
1205
1206
1207
1208
1209
1210
1211
1212
1213
1214
1215
1216
1217
1218
1219
1220
1221
1222
1223
1224
1225
1226
1227
1228
1229
1230
1231
1232
1233
1234
1235
1236
1237
1238
1239
1240
1241
1242
1243
1244
1245
1246
1247
1248
1249
1250
1251
1252
1253
1254
1255
1256
1257
1258
1259
1260
1261
1262
1263
1264
1265
1266
1267
1268
1269
1270
1271
1272
1273
1274
1275
1276
1277
1278
1279
1280
1281
1282
1283
1284
1285
1286
1287
1288
1289
1290
1291
1292
1293
1294
1295
1296
1297
1298
1299
1300
1301
1302
1303
1304
1305
1306
1307
1308
1309
1310
1311
1312
1313
1314
1315
1316
1317
1318
1319
1320
1321
1322
1323
1324
1325
1326
1327
1328
1329
1330
1331
1332
1333
1334
1335
1336
1337
1338
1339
1340
1341
1342
1343
1344
1345
1346
1347
1348
1349
1350
1351
1352
1353
1354
1355
1356
1357
1358
1359
1360
1361
1362
1363
1364
1365
1366
1367
1368
1369
1370
1371
1372
1373
1374
1375
1376
1377
1378
1379
1380
1381
1382
1383
1384
1385
1386
1387
1388
1389
1390
1391
1392
1393
1394
1395
1396
1397
1398
1399
1400
1401
1402
1403
1404
1405
1406
1407
1408
1409
1410
1411
1412
1413
1414
1415
1416
1417
1418
1419
1420
1421
1422
1423
1424
1425
1426
1427
1428
1429
1430
1431
1432
1433
1434
1435
1436
1437
1438
1439
1440
1441
1442
1443
1444
1445
1446
1447
1448
1449
1450
1451
1452
1453
1454
1455
1456
1457
1458
1459
1460
1461
1462
1463
1464
1465
1466
1467
1468
1469
1470
1471
1472
1473
1474
1475
1476
1477
1478
1479
1480
1481
1482
1483
1484
1485
1486
1487
1488
1489
1490
1491
1492
1493
1494
1495
1496
1497
1498
1499
1500
1501
1502
1503
1504
1505
1506
1507
1508
1509
1510
1511
1512
1513
1514
1515
1516
1517
1518
1519
1520
1521
1522
1523
1524
1525
1526
1527
1528
1529
1530
1531
1532
1533
1534
1535
1536
1537
1538
1539
1540
1541
1542
1543
1544
1545
1546
1547
1548
1549
1550
1551
1552
1553
1554
1555
1556
1557
1558
1559
1560
1561
1562
1563
1564
1565
1566
1567
1568
1569
1570
1571
1572
1573
1574
1575
1576
1577
1578
1579
1580
1581
1582
1583
1584
1585
1586
1587
1588
1589
1590
1591
1592
1593
1594
1595
1596
1597
1598
1599
1600
1601
1602
1603
1604
1605
1606
1607
1608
1609
1610
1611
1612
1613
1614
1615
1616
1617
1618
1619
1620
1621
1622
1623
1624
1625
1626
1627
1628
1629
1630
1631
1632
1633
1634
1635
1636
1637
1638
1639
1640
1641
1642
1643
1644
1645
1646
1647
1648
1649
1650
1651
1652
1653
1654
1655
1656
1657
1658
1659
1660
1661
1662
1663
1664
1665
1666
1667
1668
1669
1670
1671
1672
1673
1674
1675
1676
1677
1678
1679
1680
1681
1682
1683
1684
1685
1686
1687
1688
1689
1690
1691
1692
1693
1694
1695
1696
1697
1698
1699
1700
1701
1702
1703
1704
1705
1706
1707
1708
1709
1710
1711
1712
1713
1714
1715
1716
1717
1718
1719
1720
1721
1722
1723
1724
1725
1726
1727
1728
1729
1730
1731
1732
1733
1734
1735
1736
1737
1738
1739
1740
1741
1742
1743
1744
1745
1746
1747
1748
1749
1750
1751
1752
1753
1754
1755
1756
1757
1758
1759
1760
1761
1762
1763
1764
1765
1766
1767
1768
1769
1770
1771
1772
1773
1774
1775
1776
1777
1778
1779
1780
1781
1782
1783
1784
1785
1786
1787
1788
1789
1790
1791
1792
1793
1794
1795
1796
1797
1798
1799
1800
1801
1802
1803
1804
1805
1806
1807
1808
1809
1810
1811
1812
1813
1814
1815
1816
1817
1818
1819
1820
1821
1822
1823
1824
1825
1826
1827
1828
1829
1830
1831
1832
1833
1834
1835
1836
1837
1838
1839
1840
1841
1842
1843
1844
1845
1846
1847
1848
1849
1850
1851
1852
1853
1854
1855
1856
1857
1858
1859
1860
1861
1862
1863
1864
1865
1866
1867
1868
1869
1870
1871
1872
1873
1874
1875
1876
1877
1878
1879
1880
1881
1882
1883
1884
1885
1886
1887
1888
1889
1890
1891
1892
1893
1894
1895
1896
1897
1898
1899
1900
1901
1902
1903
1904
1905
1906
1907
1908
1909
1910
1911
1912
1913
1914
1915
1916
1917
1918
1919
1920
1921
1922
1923
1924
1925
1926
1927
1928
1929
1930
1931
1932
1933
1934
1935
1936
1937
1938
1939
1940
1941
1942
1943
1944
1945
1946
1947
1948
1949
1950
1951
1952
1953
1954
1955
1956
1957
1958
1959
1960
1961
1962
1963
1964
1965
1966
1967
1968
1969
1970
1971
1972
1973
1974
1975
1976
1977
1978
1979
1980
1981
1982
1983
1984
1985
1986
1987
1988
1989
1990
1991
1992
1993
1994
1995
1996
1997
1998
1999
2000
2001
2002
2003
2004
2005
2006
2007
2008
2009
2010
2011
2012
2013
2014
2015
2016
2017
2018
2019
2020
2021
2022
2023
2024
2025
2026
2027
2028
2029
2030
2031
2032
2033
2034
2035
2036
2037
2038
2039
2040
2041
2042
2043
2044
2045
2046
2047
2048
2049
2050
2051
2052
2053
2054
2055
2056
2057
2058
2059
2060
2061
2062
2063
2064
2065
2066
2067
2068
2069
2070
2071
2072
2073
2074
2075
2076
2077
2078
2079
2080
2081
2082
2083
2084
2085
2086
2087
2088
2089
2090
2091
2092
2093
2094
2095
2096
2097
2098
2099
2100
2101
2102
2103
2104
2105
2106
2107
2108
2109
2110
2111
2112
2113
2114
2115
2116
2117
2118
2119
2120
2121
2122
2123
2124
2125
2126
2127
2128
2129
2130
2131
2132
2133
2134
2135
2136
2137
2138
2139
2140
2141
2142
2143
2144
2145
2146
2147
2148
2149
2150
2151
2152
2153
2154
2155
2156
2157
2158
2159
2160
2161
2162
2163
2164
2165
2166
2167
2168
2169
2170
2171
2172
2173
2174
2175
2176
2177
2178
2179
2180
2181
2182
2183
2184
2185
2186
2187
2188
2189
2190
2191
2192
2193
2194
2195
2196
2197
2198
2199
2200
2201
2202
2203
2204
2205
2206
2207
2208
2209
2210
2211
2212
2213
2214
2215
2216
2217
2218
2219
2220
2221
2222
2223
2224
2225
2226
2227
2228
2229
2230
2231
223